



Lidget Apex Garage

- Walls - 3" thick, steel re-enforced, machine vibrated pre-cast concrete panels with Canterbury Spar pebbledash finish
- Roof - Cebrit 5' profile fibre-cement corrugated sheeted
- Garage Door - one Hermann horizontal rib fully-retractable up-and-over door in white powder coat finish
- Fascias - traditional treated timber fascias and trims
- Access Door - one timber access door
- Window - one timber framed window
- Our buildings are constructed from pre-cast concrete panels which are secured together using bolts at three points per joint, which are then sealed with industrial mastic.
- Our buildings carry a 10 year structural guarantee.
- We recommend that our buildings are erected upon a permanent concrete base of suitable thickness. We recommend a minimum of 4" thickness throughout. The base should be flat, level and square, and at least 6" longer and 6" wider than the external dimensions of the building to be supplied.



Lidget Concrete Ltd
 Albion Drive, Lidget Lane Ind. Est.,
 Thurnscoe, Rotherham S63 0BA
 Tel: 01709 881844 / Fax: 01709 881015
 Web: www.lidget.co.uk Email: sales@lidget.co.uk

Drawn by Simon Taylor
 Questions/revisions to
 simon.taylor@lidget.co.uk

Scale 1:50

Drawn: 13/05/11