



Lidget Pent Garage

Walls - 3' thick, steel re-enforced, machine vibrated pre-cast concrete panels with Canterbury Spar pebbledash finish - sand/cement fillet applied to building internal perimeter

Roof - corrugated galvanised steel roof with Grafotherm anti-condensation lining, supported on galvanised channel-section trusses, with profiled foam eaves fillers to the front and rear

Fascias - traditional treated timber fascias and trims

Garage Door - one Hormann horizontal rib steel framed fully-retractable up-and-over garage door in white powder coat finish

Dur buildings are constructed from pre-cast concrete panels which are secured together using bolts at three points per joint, which are then sealed with industrial mastic.

Dur buildings carry a 10 year structural guarantee.

We recommend that our buildings are erected upon a permanent concrete base of suitable thickness. We recommend a minimum of 4" thickness throughout. The base should be flat, level and square, and at least 6' longer and 6' wider than the external dimensions of the building to be supplied.

Copyright Lidget Concrete Ltd - not to be reproduced without express permission



Lidget Concrete Ltd
 Albion Drive, Lidget Lane Ind. Est.,
 Thurnscoe, Rotherham S63 0BA
 Tel: 01709 881844 / Fax: 01709 881015
 Web: www.lidget.co.uk Email: sales@lidget.co.uk

Drawn by Simon Taylor
 Questions/revisions to
 simon.taylor@lidget.co.uk

Scale 1:50

Drawn: 13/09/10